



# Technical Data Sheet C-90 Series

<b>Description:</b>	High Aspect Ratio Platelets in the form of gray powder								
<b>Intended Use:</b>	Coating and Plastic Industry for Trenches, Containment Vessels and Dikes, Tank Linings, Process area surfaces.								
<b>Typical Physical Properties:</b>	<table><tr><td>% Solids by Volume:</td><td>100</td></tr><tr><td>Color:</td><td>light gray</td></tr><tr><td>Shelf life:</td><td>10 years</td></tr><tr><td>Service Temperature:</td><td>-40°C to 350°C</td></tr></table> <p>Technical data should be considered representative or typical only and should not be used for specification purposes.</p>	% Solids by Volume:	100	Color:	light gray	Shelf life:	10 years	Service Temperature:	-40°C to 350°C
% Solids by Volume:	100								
Color:	light gray								
Shelf life:	10 years								
Service Temperature:	-40°C to 350°C								
<b>Limitations:</b>	None								
<b>Application Instructions:</b>	<ol style="list-style-type: none"><li>1. Apply glass flakes (C-90 series) directly to the resin, the glass flakes should account for 20%-30% of the finished product.</li><li>2. Mixing with mating part within resin's recommended working time by mixer.</li></ol>								
<b>Chemical Resistance:</b>	All kinds of Chemical materials.								
<b>Storage:</b>	Store in dry place.								
<b>Package Information</b>	Dimension per bag: 80×50×25 cm C-90 series is supplied in moisture proof paper bags, each containing 25kgs net weight. Bulk shipments are further packed in pallet boxes and protected by polythene wrapping.								
<b>Precautions:</b>	Please refer to the appropriate material safety data sheet (MSDS) prior to using this product. <b>FOR INDUSTRIAL USE ONLY</b>								
<b>Disclaimer:</b>	All information on this data sheet is based on laboratory testing and is not intended for design purposes. GlassFlakes Co.,Ltd makes no representations or warranties of any kind concerning this data.								